



# PROVE

## Series B Keypad/Reader

### Chassis

Tested to IP67

Architrave 6x2  
45mm (W) x 136mm (H) x 25mm (D)

GPO 4x3  
80mm (W) x 130mm (H) x 25mm (D)

Illuminated membrane keypad

Configurable Tricolour LED light pipes provide visual feedback

Tough polycarbonate shell and chassis for demanding outdoor environments

NPE-BDF-62R



NPE-BDF-43C



### Keypad

11 million code combinations

Locator pip to aid the visually impaired

Rugged and modern design

### Reader

Dual frequency reader

125 KHz (HID, PRESCO, EM, other formats on request)

13.56 Mhz (UID/CSN Only)

Range        Prove fob 4cm  
                 Prove card 9cm

NPE-BDF-62C

### Connectivity

Voltage: 9-28V DC  
4 & 8 bit burst mode Wiegand  
+ve/-ve LED control

Wiegand or Presco output auto detecting  
Tamper output  
DFO/DOTL buzzer

Compatible with

**PRESCO**  
**PRESCIENT**

and other Wiegand based controllers

### Other Features



Includes slide and lock mounting plate



Products can be deconstructed at the end of life and recycled.



IP and RFID features achieved without the need for potting



Advanced accelerometer anti-tamper protection.

